



REV	DESCRIPTION	DRW	DATE
A	NEW		

CIRCUIT



- NOTES:
- 1.RATING: 12VDC 50mA
  - 2.CONTACT RESISTANCE: 100mΩ Max
  - 3.INSULATION RESISTANCE: 100MΩ 250VDC FOR 1MIN
  - 4.DIELECTRIC STRENGTH: 250VAC(50/60Hz) FOR 1MIN
  - 5.LIFE TEST:100,000 CYCLES
  - 6.OPERATION FORCE&TRAVEL: SEE SPECIFICATION

P.C.B LAYOUT



6	COVER	PC
5	TERMINAL	Bronze Silver Plated
4	CONTACT	SUS
3	LED	GaAsP/GaP
2	BUTTON	POM
1	HOUSING	PA66
ITEM	PART NAME	MATERIAL

LED COLOR									
1	2	3	4	5	6	12	13	14	23
Red	Yellow	Green	Blue	White	Pure Green	Red Yellow	Red Green	Red Blue	Yellow Green

TOLERANCE		DRAWN	DATE	东莞市德沃电子科技有限公司	
UNLESS OTHERWISE STATED		CHK'D	DATE	MODEL	TS9-00TXX
X.X	±0.25	∠	±0.5'	MATL	
X.XX	±0.1	UNIT	mm	FINISH	
REV	A	SCALE	4:1		
SIZE	A4	SHEET	1 OF 1		